

## AXIS T91E61 Wall Mount

Made for fixed dome cameras



- > Small and robust design
- > For indoor and outdoor use
- > Impact and corrosion resistant

AXIS T91E61 Wall Mount is specially designed for Axis fixed dome network cameras. Neat design for both indoor and outdoor installations.

Thanks to its impact-resistant and outdoor proven material, AXIS T91E61 Wall Mount suits all environments where Axis fixed dome cameras are used in. It is designed for being mounted with Axis cameras and gives a discreet look due to its small form factor.

It is compatible with all Axis fixed dome pendant kits with a 1.5" NPS thread and can also be installed on AXIS T94R01P Conduit Back Box to enable use of cable protection conduits. With accessories it is possible to use the mount on poles, corners and on the door of AXIS T98A-VE Cabinet Series.

AXIS T91E61 has the same hole pattern as the wall mount for outdoor fixed box Axis cameras to enable an easy switch. The compatible conduit back box has the same hole pattern as AXIS T91A/T91B and AXIS T91D61 Wall Mounts, making sure that swapping two Axis cameras is as easy as possible.

Moreover, it is possible to run the cable externally by using one of the four cut-outs in the base of the wall mount.

## Technical Specifications - AXIS T91E61 Wall Mount

<b>Models</b>	AXIS T91E61 Wall Mount	<b>Casing</b>	Powder coated, chromated aluminum Color: White NCS S 1002-B Interface: 1.5" NPS
<b>General</b>		<b>Compliance</b>	RoHS, REACH, CE
<b>Supported products</b>	AXIS T94B01D Pendant Kit (AXIS M3004-V/M3005-V), AXIS T94F01D Pendant Kit (AXIS M3006-V/M3007-P/M3007-PV and AXIS M3024-LVE/M3025-VE/M3026-VE/M3027-PVE), AXIS T94F02D Pendant Kit (AXIS M3024-LVE/M3025-VE/M3026-VE/M3027-PVE), AXIS T94K01D Pendant Kit (indoor models of AXIS P32/P33/Q35), AXIS T94M01D Pendant Kit (outdoor models of AXIS Q35), AXIS T94T01D Pendant Kit (outdoor models of AXIS P32)	<b>Approvals</b>	IEC/EN/UL 60950-1, IEC/EN/UL 60950-22, EN 50581, UL 50E, IEC 62262 IK10, IEC 60721-3-4 (Class 4M4), NEMA 250 Type 4X
<b>Maximum load</b>	10 kg (22 lb)	<b>Dimensions</b>	80 x 161 x 120 mm (3.1 x 6.3 x 4.7 in)
<b>Cable routing</b>	Internal Back: Cable hole Side: Cut outs	<b>Weight</b>	525 g (1.15 lb)
<b>Environment</b>	Indoor/Outdoor	<b>Included accessories</b>	Installation Guide
		<b>Optional accessories</b>	AXIS T94R01P Conduit Back Box, AXIS T91A47 Pole Mount, VT Corner Mount WCWA, Network Cable Coupler IP66 (requires AXIS T94R01P Conduit Back Box)
		<b>Warranty</b>	Axis 3-year warranty, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a>

More information is available at [www.axis.com](http://www.axis.com)