

## AXIS Q6125-LE

### High-speed PTZ with OptimizedIR

AXIS Q6125-LE PTZ Network Camera offers discreet and unobtrusive surveillance. Its clever dome design effectively conceals the direction of the lens, and its integrated, automatically adaptable IR LED illumination enables surveillance in total darkness (up to 200 m (656 ft) or more depending on the scene). The camera provides full scene fidelity and sharp images both above and below the horizon thanks to Sharpdome technology. The speed dry function removes water drips from the dome, for clear images in rainy weather. AXIS Guard Suite analytics is included with the camera.

- > **HDTV 1080p and 30x zoom**
- > **Built-in IR LEDs with OptimizedIR**
- > **Sharpdome technology with speed dry function**
- > **WDR – forensic capture, Lightfinder and Zipstream**
- > **AXIS Guard Suite analytics included**



# AXIS Q6125-LE

<b>Models</b>	AXIS Q6125-LE 50 Hz AXIS Q6125-LE 60 Hz	PTZ: PTZ preset, guard tour, autotracking Overlay text, day/night mode IR illumination	
<b>Camera</b>			
<b>Image sensor</b>	1/2.8" Progressive scan CMOS	<b>Data streaming</b> Event data	
<b>Lens</b>	4.3–129 mm, F1.6–4.7 Horizontal field of view: 63.5°–2.3° Vertical field of view: 38.4°–1.3° Autofocus, auto-iris	<b>Built-in installation aids</b> Pixel counter	
<b>Day and night</b>	Automatically removable infrared-cut filter	<b>General</b>	
<b>Minimum illumination</b>	Color: 0.1 lux at 30 IRE, F1.6 B/W: 0.008 lux at 30 IRE, F1.6, 0 lux with IR illumination on Color: 0.15 lux at 50 IRE, F1.6 B/W: 0.01 lux at 50 IRE, F1.6, 0 lux with IR illumination on	<b>Casing</b> IK08, IP66- and NEMA 4X-rated Repaintable metal casing (aluminum), hard coated Polycarbonate (PC) clear dome with Sharpdome technology	
<b>Shutter time</b>	1/10000 s to 1 s	<b>Sustainability</b> PVC free	
<b>Pan/Tilt/Zoom</b>	Pan: 360° endless, 0.05°–700°/s Tilt: +20 to -90°, 0.05°–500°/s Zoom: 30x optical, 12x digital, total 360x zoom Nadir flip, 256 preset positions, tour recording, guard tour, control queue, on-screen directional indicator, set new pan 0°, adjustable zoom speed, speed dry	<b>Memory</b> 1 GB RAM, 512 MB Flash	
<b>Video</b>			
<b>Video compression</b>	H.264 (MPEG-4 Part 10/AVC), Main and High Profiles H.265 (MPEG-H Part 2) Motion JPEG	<b>Power</b> Axis High PoE midspan 1–port: 100–240 V AC, max 74 W Camera consumption: typical 14 W (no IR), max 51 W Axis PoE+ midspan 1–port: 100–240 V AC, max 37 W IEEE 802.3at Type 2 Class 4 Camera consumption: typical 14 W, max 25 W	
<b>Resolution</b>	1920x1080p (HDTV 1080p) to 640x360	<b>Connectors</b> RJ45 10BASE-T/100BASE-TX RJ45 Push-pull Connector (IP66)	
<b>Frame rate</b>	Up to 25/30 fps or 50/60 fps (50/60 Hz) in all resolutions	<b>IR illumination</b> Optimized IR with power-efficient, long life 850 nm IR LEDs Range of reach 200 m (656 ft) or more depending on the scene IR illumination is only enabled when powered with 60 W	
<b>Video streaming</b>	Multiple, individually configurable streams in H.264, H.265 and Motion JPEG Axis Zipstream technology in H.264 and H.265 Controllable frame rate and bandwidth VBR/MBR H.264/H.265	<b>Storage</b> Support for microSD/microSDHC/microSDXC card Support for SD card encryption Support for recording to network-attached storage (NAS) For SD card and NAS recommendations see <a href="http://www.axis.com">www.axis.com</a>	
<b>Image settings</b>	Compression, color, brightness, sharpness, white balance, exposure control, exposure zones, noise reduction, rotation, electronic image stabilization (EIS), manual shutter time, text and image overlay, image freeze on PTZ, scene profiles, focus recall Defogging, backlight compensation Contrast, highlight compensation, WDR - forensic capture: 120 dB 32 individual 3D privacy masks	<b>Operating conditions</b> With 30 W midspan: -30 °C to 50 °C (-22 °F to 122 °F) With 60 W midspan: -50 °C to 50 °C (-58 °F to 122 °F) With IR: -50 °C to 35 °C (-58 °F to 95 °F) Maximum temperature (intermittent): 60 °C (140 °F) Arctic Temperature Control: Start-up as low as -40 °C (-40 °F) Humidity 10–100% RH (condensing)	
<b>Network</b>			
<b>Security</b>	Password protection, IP address filtering, HTTPS <sup>a</sup> encryption, IEEE 802.1X <sup>a</sup> network access control, Digest authentication, User access log, Centralized Certificate Management	<b>Storage conditions</b> -40 °C to 70 °C (-40 °F to 158 °F)	
<b>Supported protocols</b>	IPv4/v6, HTTP, HTTPS <sup>a</sup> , SSL/TLS <sup>a</sup> , QoS Layer 3 DiffServ, FTP, CIFS/SMB, SMTP, Bonjour, UPnP™, SNMP v1/v2c/v3 (MIB-II), DNS, DynDNS, NTP, RTSP, RTP, SRTP, SFTP, TCP, UDP, IGMP, RTCP, ICMP, DHCP, ARP, SOCKS, SSH, NTCIP	<b>Approvals</b> EMC EN 55032 Class A, EN 55024, EN 50121-4, IEC 62236-4, EN 61000-3-2, EN 61000-3-3, EN 61000-6-1, EN 61000-6-2, FCC Part 15 Subpart B Class A, ICES-003 Class A, VCCI Class A, RCM AS/NZS CISPR32 Class A	
<b>System integration</b>			
<b>Application Programming Interface</b>	Open API for software integration, including VAPIX <sup>®</sup> and AXIS Camera Application Platform; specifications at <a href="http://www.axis.com">www.axis.com</a> AXIS Video Hosting System (AVHS) with One-Click Connection ONVIF <sup>®</sup> Profiles S and G, specifications at <a href="http://www.onvif.org">www.onvif.org</a>	<b>Safety</b> IEC/EN/UL 62368-1, IEC/EN/UL 60950-22, IEC/EN/UL 62471 risk group 2 <b>Environment</b> IEC/EN 62262 IK08, IEC/EN 60529 IP66, NEMA 250 Type 4X, IEC 60068-2-1, IEC 60068-2-2, IEC 60068-2-6, IEC 60068-2-14, IEC 60068-2-27, IEC 60068-2-30, IEC 60068-2-78, ISO 4892-2 Midspan: EN 60950-1, GS, UL, cUL, CE, FCC, VCCI, CB	
<b>Analytics</b>	AXIS Video Motion Detection, AXIS Fence Guard, AXIS Motion Guard, AXIS Loitering Guard Support for AXIS Camera Application Platform enabling installation of third-party applications, see <a href="http://www.axis.com/acap">www.axis.com/acap</a>	<b>Dimensions</b> With mounting hook: 274 x 165 x 165 mm (10 13/16 x 6 1/2 x 6 1/2 in) Without mounting hook: 256 x 165 x 165 mm (10 1/16 x 6 1/2 x 6 1/2 in)	
<b>Event triggers</b>	Detectors: live stream accessed, shock detection, day/night mode Hardware: network, temperature, fan Input Signal: manual trigger, virtual inputs PTZ: autotracking, error, moving, preset reached, ready Storage: disruption, recording System: system ready Time: recurrence, use schedule	<b>Weight</b> 3 kg (6.6 lb)	
<b>Event actions</b>	Record video: SD card and network share Pre- and post-alarm video or image buffering for recording or upload Upload of images or video clips: FTP, SFTP, HTTP, HTTPS, network share, and email Notification: email, HTTP, HTTPS, TCP, and SNMP trap	<b>Included accessories</b> IP66-rated RJ45 connector kit, AXIS High PoE 60 W SFP Midspan, installation guide, Windows decoder 1-user licence	
<p><b>Optional accessories</b> AXIS T91/T94 Mounting Accessories, Axis High PoE midspans For more accessories, see <a href="http://www.axis.com">www.axis.com</a></p> <p><b>Video management software</b> AXIS Companion, AXIS Camera Station, video management software from Axis' Application Development Partners available on <a href="http://www.axis.com/vms">www.axis.com/vms</a></p> <p><b>Languages</b> English, German, French, Spanish, Italian, Russian, Simplified Chinese, Japanese, Korean, Portuguese, Traditional Chinese</p> <p><b>Warranty</b> Axis 3-year warranty and AXIS Extended Warranty option, see <a href="http://www.axis.com/warranty">www.axis.com/warranty</a></p>			
<p>a. This product includes software developed by the OpenSSL Project for use in the OpenSSL Toolkit. (<a href="http://www.openssl.org">www.openssl.org</a>), and cryptographic software written by Eric Young (<a href="mailto:ey@cryptsoft.com">ey@cryptsoft.com</a>).</p>			
<b>Environmental responsibility:</b> <a href="http://www.axis.com/environmental-responsibility">www.axis.com/environmental-responsibility</a>			